

Safety Data Sheet

Fuax Rizzle Art Resin- HARDENER

Revision date: 2015/08/10

• Identification

Product identifier used on the label

Fuax Rizzle Art Resin **HARDENER**

Recommended use of the chemical and restriction on use

Floor Coating. Industrial Maintenance Coating.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

Countertop Epoxy
2530 East Foresight Circle
Grand Junction, CO 81505

970-639-9338

Emergency telephone number

CHEMTREC: 1-800-424-9300

Other means of identification

Chemical family: mixed amine
Synonyms: mixed amine

• Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Acute Toxicity - Oral	Category 4
Skin Corrosion	Category 1B
Serious Eye Damage	Category 1
Skin Sensitization -	Category 1

Label Elements

Pictogram:



Safety Data Sheet Fuax Rizzle Art Resin- HARDENER

Revision date: 2015/08/10

Signal Word: Danger

Hazard Statement:

Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.

Precautionary Statements (Prevention):

Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash hands thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements (Response):

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

IF ON SKIN: Remove contaminated clothing and shoes. Rinse immediately with plenty of water. Get medical attention if irritation occurs. Rinse skin with water/shower.

Precautionary Statements (Disposal):

Disposal of contents/container to be specified in accordance with regulations.

Hazards not otherwise classified

Harmful if swallowed.
Components of the product may affect the nervous system.
Severe respiratory irritant.
Severe skin irritant.
Severe eye irritant.
May cause sensitization by skin contact.

- Composition / Information on Ingredients**

Components	CAS Number	Concentration (Weight)
Benzyl alcohol	100-51-6	< 40 %
Isophoronediamine (IPD)	2855-13-2	< 35 %
Trimethylhexamethylenediamine (TMD)	25620-58-0	< 10 %
Cycloaliphatic amine	Not Available	> 15%
Proprietary Ingredients	Proprietary	< 15 %

CHEMICAL FAMILY: Cycloaliphatic Amine

Safety Data Sheet

Fuax Rizzle Art Resin- HARDENER

Revision date: 2015/08/10

• First-Aid Measures

Description of first aid measures

General advice:

Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.

If inhaled:

If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Move to fresh air.

If on skin:

Immediately remove contaminated clothing, and any extraneous chemical, if possible to do so without delay. Take off contaminated clothing and shoes immediately.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Never give anything by mouth. Prevent aspiration of person. Turn person's head to the side. on his back, place

Most important symptoms and effects, both acute and delayed:

Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat. Neurological disorders. Asthma. Skin disorders and Allergies. Eye disease.

Note to physician

Treatment: Application of corticosteroid cream has been effective in treating skin irritation.

• Fire-Fighting Measures

Extinguishing media

Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical. Dry sand. Limestone powder.

Special hazards arising from the substance or mixture

May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from fire-fighting to enter drains or water courses. Incomplete combustion may form carbon monoxide. Downwind personnel must be evacuated. Burning produces noxious and toxic fumes.

Safety Data Sheet

Fuax Rizzle Art Resin- HARDENER

Revision date: 2015/08/10

Advice for fire-fighters

Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Wear self-contained breathing apparatus for firefighting if necessary.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Impact Sensitivity:

Remarks: No data available.

- **Accidental release measures**

Personal precautions, protective equipment and emergency procedures

Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.

Environmental precautions

Construct a dike to prevent spreading

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

- **Handling and Storage**

Handling

Do not use sodium nitrite or other nitrosating agents in formulations containing this product. Suspected cancer-causing nitrosamines could be formed. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Avoid contact with eyes. Use only in well-ventilated areas. Avoid breathing vapors and/or aerosols. Use personal protective equipment. When using, do not eat, drink or smoke.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Segregate from acids and acid forming substances.

Further information on storage conditions: Containers should be stored tightly sealed in a dry place. Keep container tightly closed and in a well-ventilated place. Keep away from sources of ignition - No smoking. Keep container tightly closed.

Storage stability: Do not store in reactive metal containers. Keep container dry because product takes up the humidity of air.

Safety Data Sheet

Fuax Rizzle Art Resin- HARDENER

Revision date: 2015/08/10

- **Exposure Controls/Personal Protection**

Engineering Measures

Provide readily accessible eye wash stations and safety showers.
Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapor/particulate respirator when ventilation is inadequate. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. For emergency or non-routine, high exposure situations, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection:

Butyl-rubber, nitrile rubber, neoprene, PVC disposable, or otherwise impervious gloves should be worn. Chemical resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit, long-sleeve shirts, trousers without cuffs.

General safety and hygiene measures:

Eye wash fountains and safety showers must be easily accessible. Wear protective clothing as necessary to prevent contact. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). Hands and/or face should be washed before breaks and at the end of the shift. When using, do not eat, drink or smoke. Remove contaminated clothing. Discard contaminated leather articles.

Exposure limit(s)

Benzyl alcohol	Time Weighted Average (TWA): WEEL	10 ppm	44.20 mg/m ³
----------------	-----------------------------------	--------	-------------------------

- **Physical and Chemical Properties**

Form: liquid

Safety Data Sheet Fuax Rizzle Art Resin- HARDENER

Revision date: 2015/08/10

Odor:	Ammoniacal
Color:	Clear, Colorless
pH value:	Alkaline, 11-12
Melting point:	No data available
Boiling point:	> 200 °C
Flash point:	> 90 °C (ASTM D93)
Flammability:	Not flammable
Lower explosion limit:	Not applicable
Upper explosion limit:	Not applicable
Autoignition:	No data available
Vapor pressure:	< 1.00 mmHg at 70 °F (21 °C)
Density:	61.804 lb/ft ³ (0.99 g/cm ³) at 70 °F (21 °C)
Viscosity, Dynamic	1500-2000 CPS
Solubility in Water	Not very soluble < 1%
Evaporation rate:	< Ether

• Stability and Reactivity

Chemical Stability:
Stable under normal conditions.

Conditions to avoid:
No data available.

Materials to avoid:
Sodium hypochlorite. CAUTION! N-Nitrosamines, many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations. Nitrous acid and other nitrosating agents. Reactive metals (e.g. sodium, calcium, zinc etc.). Materials reactive with hydroxyl compounds. Organic acids (i.e. acetic acid, citric acid etc.). Mineral acids. Product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Oxidizing agents.

Hazardous decomposition products:
Aldehydes. Flammable hydrocarbon fragments. Nitrosamine. Nitrogen oxides (NO_x). Nitrogen oxide can react with water vapors to form corrosive nitric acid. Ammonia. Nitric acid. Carbon monoxide. Carbon dioxide (CO₂)

Possibility of hazardous Reactions/Reactivity:

Safety Data Sheet

Fuax Rizzle Art Resin- HARDENER

Revision date: 2015/08/10

No data available.

- Toxicological information**

Information on toxicological effects

Likely routes of exposure

Effects on Eye:

Severe eye irritation.

Effects on Skin :

If absorbed through the skin, may cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties.

Inhalation Effects:

May cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties. Severe cases of overexposure can result in respiratory failure. May cause nose, throat, and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.

Ingestion Effects:

Harmful if swallowed. May cause central nervous system effects, such as headache, nausea, vomiting, abdominal pain, dizziness, confusion, breathing difficulties. Severe cases of overexposure can result in respiratory failure.

Symptoms:

Acute toxicity

Acute Oral Toxicity:

Respiratory and Central Nervous System Effects: May cause dizziness, confusion, headache, nausea, vomiting, abdominal pain, breathing difficulties, and/or

LD50 : 1,000 mg/kg Species : Rat.

Inhalation:

No data is available on the product itself. Inhalation - Components
Benzyl alcohol: LC50 (4 h): > 4.178 mg/l OECD Test Guideline 403
Species: Rat.

Acute Dermal Toxicity:

LD50 : > 2,800 mg/kg Species : Rabbit.

Skin corrosion/irritation:

Severe skin irritation. Corrosive to the skin of a rabbit.

Serious Eye Damage/Eye Irritation:

Severe eye irritation

Sensitization:

May cause sensitization by skin contact

Chronic Toxicity or Effects from Long Term Exposures

Carcinogenicity:

No data available

Reproductive Toxicity:

No data is available on the product itself

Safety Data Sheet Fuax Rizzle Art Resin- HARDENER

Revision date: 2015/08/10

Germ Cell Mutagenicity: No data is available on the product itself

Specific Target Organ Systemic Toxicity (single exposure): No data is available

Specific Target Organ Systemic Toxicity (repeated exposure): No data is available

~~This product contains chemicals known to the State of California to cause cancer or reproductive toxicity.~~

- **Ecological Information**

EcoToxicity Effects

Aquatic toxicity: No data available on the product itself

Toxicity to fish:

Benzyl alcohol LC50 (96 h) : 10 mg/l Species : Bluegill sunfish (*Lepomis macrochirus*).

Benzyl alcohol LC50 (96 h) : 460 mg/l Species : Fathead minnow (*Pimephales promelas*).

Toxicity to algae:

Benzyl alcohol IC50 (72 h) : 700 mg/l Species : Algae.

Toxicity to other organisms: No data available.

Persistence and degradability

Biodegradability: No data is available on the product itself.

Mobility: No data available.

Bioaccumulation: No data is available on the product itself.

Bioaccumulation:

Benzyl alcohol: Low bioaccumulation potential.

- **Disposal Considerations**

Dispose of in a licensed facility. Do not discharge into waterways or sewer systems without proper authorization. Dispose in accordance with all applicable regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Container disposal:

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

- **Transport Information**

Safety Data Sheet

Fuax Rizzle Art Resin- HARDENER

Revision date: 2015/08/10

Land transport

USDOT

Hazard class: 8
 Packing group: III
 ID number: UN 2735
 Hazard label: 8
 Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S., (Trimethylhexane-1,6-diamine)
 Marine Pollutant: No

Sea transport

IMDG

Hazard class: 8
 Packing group: III
 ID number: UN 2735
 Hazard label: 8
 Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S., (Trimethylhexane-1,6-diamine)
 Marine Pollutant: No

Air transport

IATA/ICAO

Hazard class: 8
 Packing group: III
 ID number: UN 2735
 Hazard label: 8
 Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S., (Trimethylhexane-1,6-diamine)
 Marine Pollutant: No

• Regulatory Information

Toxic Substance Control Act (TSCA) 12(b)

Component(s): None.

COUNTRY	REGULATORY LIST	NOTIFICATION
USA	TSCA	Included on Inventory.
EU	EINECS	EINECS
Canada	DSL	Included on Inventory.

Safety Data Sheet

Fuax Rizzle Art Resin- **HARDENER**

Revision date: 2015/08/10

Australia	AICS	Included on Inventory.
Japan	ENCS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification:
Acute Health Hazard

EPA SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level:
None.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

- **Other Information**

HMIS Rating

Health : 3
Flammability : 1
Physical hazard : 0

SDS Prepared by:

Countertop Epoxy

The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication as part of Countertop Epoxy Product Safety Program. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information obtained herein. Data sheets are available for all Countertop Epoxy products. You are urged to obtain data sheets for all Countertop Epoxy products you buy, process, use or distribute and you are encouraged and requested to advise those who may come in contact with such products of the information contained therein.

To determine applicability or effects of any law or regulation with respect to the product, user should consult his legal advisor or the appropriate government agency. Countertop Epoxy does not undertake to furnish advice on

Safety Data Sheet

Fuax Rizzle Art Resin- HARDENER

Revision date: 2015/08/10

such matters.