

## Safety Data Sheet FX Casting Resin- HARDENER

Revision date: 2015/11/18

### • Identification

Product identifier used on the label

## FX Casting Resin HARDENER

Recommended use of the chemical and restriction on use:

**Floor Coating. Industrial Maintenance Coating.**

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

### Details of the supplier of the safety data sheet

Company:

Countertop Epoxy  
2530 East Foresight Circle  
Grand Junction, CO 81505

970-639-9338

### Emergency telephone number

CHEMTREC: 1-800-424-9300

### Other means of identification

Chemical family: mixed amine  
Synonyms: mixed amine

### • Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200**

### Classification of the product

Met. Corrosion	Category 1
Acute Toxicity - Oral	Category 4
Skin Corrosion	Category 2
Serious Eye Damage	Category 1
Skin Sensitization -	Category 1

Label Elements

Pictogram:



## Safety Data Sheet FX Casting Resin- HARDENER

Revision date: 2015/11/18

Signal Word: Danger

**Hazard Statement:**

May be corrosive to metals  
Harmful if swallowed.  
Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.

**Precautionary Statements (Prevention):**

Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash hands thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary Statements (Response):**

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

IF ON SKIN: Rinse immediately. If severe, get medical attention. IF IN EYES: Rinse continuously with water for at least 15 minutes. IF INHALED: Remove to fresh air. If severe, get medical attention. IF ON CLOTHING: Remove contaminated clothing. Rinse skin with water/shower.

**Precautionary Statements (Disposal):**

Disposal of contents/container to be specified in accordance with regulations.

**Hazards not otherwise classified**

Harmful if swallowed.  
Components of the product may affect the nervous system.  
Severe respiratory irritant.  
Severe skin irritant.  
Severe eye irritant.  
May cause sensitization by skin contact.

### • Composition / Information on Ingredients

Components	CAS Number	Concentration (Weight)
Polyetheramine	39423-51-3	< 50 %
Benzyl alcohol	100-51-6	< 50 %
Isophoronediamine (IPD)	2855-13-2	< 25 %
Nonylphenol	84852-15-3	< 25 %
Trimethylhexamethylenediamine (TMD)	25620-58-0	< 25 %
Proprietary	Proprietary	< 15 %

## Safety Data Sheet FX Casting Resin- HARDENER

Revision date: 2015/11/18

CHEMICAL FAMILY: Cycloaliphatic Amine

### • First-Aid Measures

#### Description of first aid measures

##### General advice:

Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.

##### If inhaled:

If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Move to fresh air.

##### If on skin:

Immediately remove contaminated clothing, and any extraneous chemical, if possible to do so without delay. Take off contaminated clothing and shoes immediately.

##### If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

##### If swallowed:

Never give anything by mouth to an unconscious person. Turn person's head to the side. on his back, place

##### Most important symptoms and effects, both acute and delayed:

Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat. Neurological disorders. Asthma. Skin disorders and Allergies. Eye disease.

##### Note to physician

Treatment: Application of corticosteroid cream has been effective in treating skin irritation.

### • Fire-Fighting Measures

#### Extinguishing media

Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical. Dry sand. Limestone powder.

#### Special hazards arising from the substance or mixture

May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the

## Safety Data Sheet FX Casting Resin- HARDENER

Revision date: 2015/11/18

formation of very toxic aqueous solutions. Do not allow run-off from fire-fighting to enter drains or water courses. Incomplete combustion may form carbon monoxide. Downwind personnel must be evacuated. Burning produces noxious and toxic fumes.

### **Advice for fire-fighters**

Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Wear self-contained breathing apparatus for firefighting if necessary.

### **Further information:**

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### **Impact Sensitivity:**

Remarks: No data available.

- **Accidental release measures**

### **Personal precautions, protective equipment and emergency procedures**

Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.

### **Environmental precautions**

Construct a dike to prevent spreading

### **Methods and material for containment and cleaning up**

Spills should be contained, solidified, and placed in suitable containers for disposal.

- **Handling and Storage**

### **Handling**

Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Avoid contact with eyes. Use only in well-ventilated areas. Avoid breathing vapors and/or aerosols. Use personal protective equipment. When using, do not eat, drink or smoke.

Protection against fire and explosion:

Take precautionary measures against static discharges.

### **Conditions for safe storage, including any incompatibilities**

Segregate from acids and acid forming substances.

Further information on storage conditions: Containers should be stored tightly sealed in a dry place. Keep container tightly closed and in a well-ventilated place. Keep away from sources of ignition - No smoking. Keep container tightly closed.

## Safety Data Sheet FX Casting Resin- HARDENER

Revision date: 2015/11/18

Storage stability: Do not store in reactive metal containers. Keep container dry because product takes up the humidity of air.

### Exposure Controls/Personal Protection

#### Engineering Measures

Provide readily accessible eye wash stations and safety showers.

Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits

#### Personal protective equipment

##### Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapor/particulate respirator when ventilation is inadequate. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. For emergency or non-routine, high exposure situations, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

##### Hand protection:

Butyl-rubber, nitrile rubber, neoprene, PVC disposable, or otherwise impervious gloves should be worn. Chemical resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

##### Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles).

##### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit, long-sleeve shirts, trousers without cuffs.

##### General safety and hygiene measures:

Eye wash fountains and safety showers must be easily accessible. Wear protective clothing as necessary to prevent contact. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). Hands and/or face should be washed before breaks and at the end of the shift. When using, do not eat, drink or smoke. Remove contaminated clothing. Discard contaminated leather articles.

#### Exposure limit(s)

Benzyl alcohol	Time Weighted Average (TWA): WEEL	10 ppm	44.20 mg/ m3
----------------	-----------------------------------	--------	-----------------

### Physical and Chemical Properties

Form: liquid

## Safety Data Sheet FX Casting Resin- HARDENER

Revision date: 2015/11/18

Odor:	Ammoniacal
Color:	Clear, Colorless
pH value:	Alkaline, 11-12
Melting point:	No data available
Boiling point:	> 210 °C
Flash point:	> 100 °C (ASTM D93)
Flammability:	Not flammable
Lower explosion limit:	Not applicable
Upper explosion limit:	Not applicable
Autoignition:	No data available
Vapor pressure:	< 1.00 mmHg at 70 °F (21 °C)
Density:	61.804 lb/ft <sup>3</sup> (0.99 g/cm <sup>3</sup> ) at 70 °F (21 °C)
Viscosity, Dynamic	1500-2000 CPS
Solubility in Water	Not very soluble < 1%
Evaporation rate:	< Ether

### • Stability and Reactivity

Corrosion to metals:  
May be corrosive to metals

Chemical Stability:  
Stable under normal conditions.

Conditions to avoid:  
No data available.

Materials to avoid:

Sodium hypochlorite. CAUTION! N-Nitrosamines, many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations. Nitrous acid and other nitrosating agents. Reactive metals (e.g. sodium, calcium, zinc etc.). Materials reactive with hydroxyl compounds. Organic acids (i.e. acetic acid, citric acid etc.). Mineral acids. Product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Oxidizing agents.

Hazardous decomposition products:

Aldehydes. Flammable hydrocarbon fragments. Nitrosamine. Nitrogen oxides (NO<sub>x</sub>). Nitrogen oxide can react with water vapors to form corrosive nitric acid. Ammonia. Nitric acid. Carbon monoxide. Carbon

## Safety Data Sheet FX Casting Resin- HARDENER

Revision date: 2015/11/18

dioxide (CO2)

Possibility of hazardous Reactions/Reactivity:

No data available.

### • Toxicological information

Information on toxicological effects

Likely routes of exposure

Effects on Eye:

Severe eye irritation.

Effects on Skin :

If absorbed through the skin, may cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties.

Inhalation Effects:

May cause central nervous system effects, such as headache, nausea, dizziness, confusion, breathing difficulties. Severe cases of overexposure can result in respiratory failure. May cause nose, throat, and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.

Ingestion Effects:

Harmful if swallowed. May cause central nervous system effects, such as headache, nausea, vomiting, abdominal pain, dizziness, confusion, breathing difficulties. Severe cases of overexposure can result in respiratory failure.

Symptoms:

Acute toxicity

Acute Oral Toxicity: LD50 : > 50 - < 200 mg/kg Species : Rat.

Inhalation:

No data is available on the product itself. Inhalation - Components  
Benzyl alcohol: LC50 (4 h): > 4.178 mg/l OECD Test Guideline 403  
Species: Rat.

Acute Dermal Toxicity:

LD50 : > 2,000 mg/kg Species : Rabbit.

Skin corrosion/irritation:

Severe skin irritation. Corrosive to the skin of a rabbit.

Serious Eye Damage/Eye Irritation:

Severe eye irritation

Sensitization:

May cause sensitization by skin contact

Chronic Toxicity or Effects from Long Term Exposures





## Safety Data Sheet FX Casting Resin- HARDENER

Revision date: 2015/11/18

### • Transport Information

#### Land transport

USDOT

Hazard class: 8  
 Packing group: III  
 ID number: UN 2735  
 Hazard label: 8  
 Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S., (Trimethylhexane-1,6-diamine)  
 Marine Pollutant: No

#### Sea transport

IMDG

Hazard class: 8  
 Packing group: III  
 ID number: UN 2735  
 Hazard label: 8  
 Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S., (Trimethylhexane-1,6-diamine)  
 Marine Pollutant: No

#### Air transport

IATA/ICAO

Hazard class: 8  
 Packing group: III  
 ID number: UN 2735  
 Hazard label: 8  
 Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S., (Trimethylhexane-1,6-diamine)  
 Marine Pollutant: No

### • Regulatory Information

Toxic Substance Control Act (TSCA) 12(b)

Component(s): None.

COUNTRY	REGULATORY LIST	NOTIFICATION
USA	TSCA	Included on Inventory.
EU	EINECS	Included on Inventory.

## Safety Data Sheet FX Casting Resin- HARDENER

Revision date: 2015/11/18

Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
Japan	ENCS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification:  
Acute Health Hazard

EPA SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level:  
None.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

- **Other Information**

### HMIS Rating

Health : 3  
Flammability : 1  
Physical hazard : 0

### SDS Prepared by:

Countertop Epoxy

The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication as part of Countertop Epoxy Product Safety Program. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information obtained herein. Data sheets are available for all Countertop Epoxy products. You are urged to obtain data sheets for all Countertop Epoxy products you buy, process, use or distribute and you are encouraged and requested to advise those who may come in contact with such products of the information contained therein.

To determine applicability or effects of any law or regulation with respect to the product, user should consult his legal advisor or the appropriate government agency. Countertop Epoxy does not undertake to furnish advice on such matters.